

Laser Marking Machine L Series

ONE&1 CO₂ / Fiber / Green / UV

- Features**
- Inspection for overlapped marking prevention
 - Z clamp for maintaining uniform marking quality
 - Maximized productivity with speediest cycle time
 - Maximum use of dust collector function
 - Automatic data back up



Model	L 7000 Advanced Model	L 5000 Basic Model	L 3000 Faster Model
Dimension (L x D x W)	1160 x 1500 x 1710 mm 1300 x 1500 x 1710 mm	1160 x 1500 x 1710 mm 1300 x 1500 x 1710 mm	800 x 1250 x 1710 mm 1100 x 1250 x 1710 mm
Marking area (X x Y)	400 x 300 mm 600 x 400 mm	400 x 300 mm 600 x 400 mm	300 x 300 mm
Type	X and Y adjustable	X and Y adjustable	X and Y fixed
Width adjustment	Mandatory option	Mandatory option	Mandatory option
Z axis calibration	Mandatory option	Option	Option
Vision camera	o	o	Option
Electric power	110~220 V 50~60Hz	110~220 V 50~60Hz	110~220 V 50~60Hz
Option	MES link Rollover unit embedded Dual line	MES link Rollover unit embedded Dual line	MES link Vision camera Rollover unit embedded Dual line